

T2 Topless® X2

4-Post Cable Lifts

Capacity: 9,000 lbs – 30,000 lbs

Preserve your view with our **T2 Topless® X2**! No top rail to spoil the waterfront vistas, plus all the safety and durability of our other lifts at **twice the speed!**



Warranty

- 15-year structural warranty
- 5-year gear box warranty
- 2-year motor warranty
- 1-year comprehensive warranty

Standard Features

- Patented, sealed aluminum Hi-Tide X2 Gear Drive® provides efficient, quiet performance at twice the speed of our standard gear box
- High-speed operation: lifts 9,000 to 20,000 lb. at up to 4 ½ feet per minute
- Remote control limit switch
- Aluminum bunks (up to 20,000 lbs)
- All 6061-T6 marine-grade aluminum and stainless steel construction
- Machined aluminum cable winders that extend cable life
- Stainless steel electric motors – made in America
- Cable Keepers

Options & Accessories

- Aluminum catwalk
- Aluminum catwalk steps
- Aluminum service platform
- Boarding platform
- Lexan Winder Covers
- Additional options and accessories available

Specifications for the T2 Topless® X2

All specifications subject to change without notice.

Structural Specifications for T2 Topless® X2

LIFT MODEL	LIFTER BEAM DIMENSIONS	MAXIMUM BEAM	SPEED	CABLE SIZE (STAINLESS STEEL)	GEAR BOX	STANDARD BUNKS	MOTOR (STAINLESS STEEL)	REQUIRED VOLTS/AMPS	GUIDE POLE WEIGHT PIPE SIZE	PILING QUANTITY/SIZE
9,000 LB (DOUBLE CABLE)	6" x 4" x 12'6"	9'6"	54"/min	1/4" x 30'	Standard duty Gear Drive®	8" x 14' Aluminum	(4) 3/4 hp	220V/30A	2" x 6'8" 1.5" x 50"	4 pilings/ 10" diameter
12,000 LB (DOUBLE CABLE)	8" x 5" x 12'6"	9'6"	54"/min	5/16" x 30'	Standard duty Gear Drive®	10" x 14' Aluminum	(4) 1 hp	220V/30A	2" x 10' 1.5" x 100"	4 pilings/ 10" diameter
16,000 LB (DOUBLE CABLE)	10" x 6" x 14'	11'0"	54"/min	5/16" x 30'	Heavy duty Gear Drive®	10" x 14' Aluminum	(4) 1 1/2 hp	220V/50A	2" x 10' 1.5" x 100"	4 pilings/ 10" diameter
20,000 LB (DOUBLE CABLE)	10" x 6" x 14'	11'0"	54"/min	3/8" x 30'	Heavy duty Gear Drive®	10" x 14' Aluminum	(4) 2 hp	220V/60A	2" x 10' 1.5" x 100"	4 pilings/ 10" diameter
24,000 LB (TRIPLE CABLE)	12" x 7" x 16' Light duty	12'6"	36"/min	5/16" x 45'	Heavy duty Gear Drive®	3" x 12" x 18' Wood	(4) 1 1/2 hp	220V/50A	2" x 10' 1.5" x 100"	4 pilings/ 12" diameter
30,000 LB (TRIPLE CABLE)	12" x 7" x 16' Heavy duty	12'6"	36"/min	3/8" x 50'	Heavy duty Gear Drive®	3" x 12" x 18' Wood	(4) 2 hp	220V/60A	2" x 10' 1.5" x 100"	4 pilings/ 12" diameter

Wire Specifications for the T2 Topless® X2

MOTOR HP (STAINLESS STEEL)	100'/240V	200'/240V	300'/240V	400'/240V
(4) 3/4 hp or 1 hp	#10	#8	#6	#4
(4) 1 1/2 hp	#8	#6	#4	#2
(4) 2 hp	#8	#4	#4	#2

Piling Setting Dimensions for the T2 Topless® X2

